

B

## TITLE

A microprocessor controlled toy building element with visual programming

B

~~BACKGROUND OF THE INVENTION~~

## B FIELD OF THE INVENTION

This invention relates to a microprocessor controlled toy building element comprising a microprocessor which can execute instructions in the form of a program stored in a memory; a display integrated in the toy; coupling means for coupling with building elements which can be moved by manoeuvring means, said manoeuvring means being controllable in response to the instructions.

B

~~DESCRIPTION OF THE PRIOR ART~~

In connection with the development of small, sophisticated and relatively inexpensive microprocessors it has become attractive to use these in many different consumer products - including toys. Generally, the development of toys has proceeded from simple functions such as playing of sounds in dolls, performance of simple patterns of movement in robots, etc., to the development of toys with sophisticated behaviour. The sophisticated behaviour can be recognized by a child playing with the toy and give the impression of a kind of personality. Particularly in connection with construction toys there are many possibilities of giving the toy a behaviour by combining program steps for a microprocessor controlled toy building element with a self-built mechanical structure.

Such programmable construction toys are known from the product ROBOTICS INVENTION SYSTEM from LEGO MINDSTORMS, which is a toy which can be programmed by a computer to detect a plurality of physical signals and to respond to these signals by implementing physical actions. The toy may e.g. be incorporated as a component in a vehicle by combining the toy with other toy building elements, e.g. motors, wheels, collision detectors and light detectors.

WO 90/02983 relates to a robot toy element which is controlled by a microprocessor and which can be programmed via an incorporated keyboard. The robot toy element can  
5 move according to patterns of movement and respond to external influences.

US 5,724,074 is an example of a toy element which can be programmed. The toy element can be programmed from an external computer by means of a graphic user interface.  
10

The above-mentioned principles of programming toy elements, however, are inexpedient for use in microprocessor controlled toy building elements. Particularly when the  
15 microprocessor controlled toy building elements can be coupled with other building elements to form a structure which can perform a pattern of movement, which depends partly on the structure and partly on the program performed by the microprocessor controlled toy building element. In such a situation, a change in the structure after  
20 it has been programmed may result in a structure which does not work. This is evident to adults, but to children who play in an intuitive - and partly unstructured - way, this will none the less be a typical situation. The known toy cannot handle such situations in a  
25 satisfactory manner.

In view of the prior art in the field, it is a problem that the programming and control facilities for microprocessor controlled toy building elements are insufficient.  
30

3 *BRIEF SUMMARY OF THE INVENTION*

Accordingly, an object of the invention is to provide improved programming and control facilities for such microprocessor controlled toy building elements.

5 This is achieved when the microprocessor controlled toy building element mentioned initially is characterized in that the display comprises a plurality of icons which each represent instructions for the microprocessor, and which can be activated by a user for programming of the  
10 microprocessor, and by signalling with a first one of the plurality of icons, said first icon representing instructions which the microprocessor is executing.

This ensures that the user of the toy receives an indication of which instructions, rules or program steps the  
15 microprocessor is programmed to execute - and executes while signalling with the icon. This makes it easy for the child to proceed by the method of trial and error and get assistance in finding errors, if any, in the program  
20 or in the structure.

It is thus possible to program a toy element in a simple manner. It is moreover possible to make the toy element perform sophisticated functions based on a few and intuitive activations from a user.  
25

3 *BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS*

A preferred embodiment of the invention will be described below with reference to the drawing, in which

30 fig. 1 shows a block diagram of a programmable toy element;

fig. 2 shows a display on a toy element;

fig. 3a shows a first diagram of a state machine for visual programming of a toy element;

fig. 3b shows a second diagram of a state machine for visual programming of a toy element;

fig. 3c shows a third diagram for interrupting a state machine;

fig. 3d shows a fourth diagram for starting a state machine;

fig. 4 shows parallel and sequential execution of programs;

fig. 5 shows first and second toy elements, where the first toy element can transfer data to the second toy element; and

fig. 6 shows a toy structure comprising a microprocessor controlled toy building element according to the invention coupled with generally known toy building elements.

### DETAILED DESCRIPTION OF THE INVENTION

Fig. 1 shows a block diagram of a programmable toy element. The toy element 101 comprises a plurality of electronic means for programming the toy element so that it can affect electronic units (e.g. motors) in response to signals picked up from various electronic sensors (e.g. electrical switches).

The toy element may hereby be caused to perform sophisticated functions such as e.g. action controlled movement, provided that the toy element is combined with the electronic units/sensors in a suitable manner.

The toy element 101 comprises a microprocessor 102 which is connected to a plurality of units via a communications bus 103. The microprocessor 102 can receive data via the communications bus 103 from two A/D converters "A/D input #1" 105 and "A/D input #2" 106. The A/D converters can pick up discrete multibit signals or simple binary signals. Further, the A/D converters are adapted to detect passive values such as e.g. ohmic resistance.

The microprocessor 102 can control electronic units such as e.g. an electric motor (not shown) via a set of terminals "PWM output #1" 107 and "PWM output #2" 108. In a preferred embodiment of the invention the electronic units are controlled by a pulse width modulated signal.

Moreover, the toy element can emit sound signals or sound sequences by controlling a sound generator 109, e.g. a loudspeaker or piezoelectric unit.

The toy element can emit light signals via the light source "VL output" 110. These light signals can be emitted by means of light emitting diodes. The light emitting diodes may e.g. be adapted to indicate various states of the toy element and the electronic units/sensors. The light signals may furthermore be used as communications signals for other toy elements of a corresponding type. The light signals may e.g. be used for transferring data to a second toy element via a light guide.

The toy element can receive light signals via the light detector "VL input" 111. These light signals may be used inter alia for detecting the intensity of the light in the room in which the toy element is present. The light

signals may alternatively be received via a light guide and represent data from a second toy element or a personal computer. The same light detector may thus have the function of communicating via a light guide and of serving as a light sensor for detecting the intensity of the light in the room in which the toy element is present.

In a preferred embodiment, the "VL input" 111 is adapted to selectively either communicate via a light guide or alternatively to detect the intensity of the light in the room in which the toy element is present.

Via the infrared light detector "IR input/output" 112 the toy element can transfer data to other toy elements or receive data from other toy elements or e.g. a personal computer.

The microprocessor 102 uses a communications protocol for receiving or transmitting data.

The display 104 and the keys "shift" 113, "run" 114, "select" 115 and "start/interrupt" 116 constitute a user interface for operating/programming the toy element. In a preferred embodiment, the display is an LCD display that can show a plurality of specific icons or symbols. The appearance of the symbols on the display may be controlled individually, e.g. an icon may be visible, be invisible and be caused to flash.

By affecting the keys the toy element may be programmed at the same time as the display provides feedback to a user about the program which is being generated or executed. This will be described more fully below. As the user interface comprises a limited number of elements

(that is a limited number of icons and keys), it is ensured that a child who wants to play with the toy will quickly learn how to operate it.

- 5 The toy element also comprises a memory 117 in the form of RAM and ROM. The memory contains an operating system "OS" 118 for control of the basic functions of the microprocessor, a program control "PS" 119 capable of controlling the execution of user-specified programs, a plurality of rules 120, each rule consisting of a plurality of specific instructions for the microprocessor, and a program 121 in RAM which utilizes the specific rules.

- 10 In a preferred embodiment, the toy element is based on a so-called single chip processor which comprises a plurality of inputs and outputs, a memory and a microprocessor in a single integrated circuit.

- 15 In a preferred embodiment, the toy element comprises light emitting diodes which can indicate the direction of revolution of connected motors.

- 20 In a further embodiment, the toy element comprises incorporated manoeuvring means in the form of e.g. one or more motors with take-off in the form of shafts that are driven by the motors, or in the form of coupling holes with means for receiving part of a shaft and rotating this shaft.

- 25 Fig. 2 shows a display on a toy element. The display 201 is adapted to show a plurality of specific icons and is shown in a state in which all the icons have been made visible. The icons are divided by horizontal and vertical beams 202 and 203, respectively, into a plurality of

groups 204, 205, 206, 207 and 208 according to their function.

5 The icons may e.g. be designed to illustrate possible patterns of movement for a vehicle. A vehicle may e.g. be constructed by combining the toy element with two motors which can drive a set of wheels at the right-hand side and the left-hand side, respectively, of a vehicle. The vehicle may hereby be controlled to drive forwards, back-  
10 wards, to the left and to the right. Further, the vehicle may comprise pressure-sensitive switches for detecting collision and light-sensitive sensors.

15 The group 204 includes icons for a straight and forwardly directed pattern of movement, a forwardly directed zigzag pattern of movement, a circular movement and a movement which repeats a given pattern. These patterns of movement are not conditioned by the action of sensors and are therefore unconditioned.

20 The group 205 includes a first icon for a pattern of movement, which is reversed when an obstacle is detected. A second icon shows a straight and forwardly directed pattern of movement, where the forwardly directed movement is merely corrected by the detection of an obstacle.  
25 A third icon conditions initiation of a pattern of movement. A fourth icon stops an ongoing pattern of movement when a pressure sensor is activated. The icons in the group 205 thus represent patterns of movement which are  
30 conditioned by pressure-sensitive sensors.

The group 206 includes icons for starting a pattern of movement which moves toward the strongest light intensity and a pattern of movement which moves toward the weakest



light intensity, respectively. The light intensity is detected by means of light-sensitive sensors. The icons in the group 205 thus represent patterns of movement which are conditioned by light-sensitive sensors.

5

The group 207 includes three identical icons which can be displayed in combination to indicate the time constant at which the mentioned patterns of movement are to be performed. For example, the zigzag pattern may be modified by stepwise changing the period of time which has to elapse before the direction is changed. The time constant may e.g. be 2 seconds, 4 seconds and 7 seconds.

10

The group 208 comprises icons which represent a plurality of special effects. These effects may e.g. comprise emission of various sound and light signals optionally combined with an arbitrary activation of the mentioned patterns of movement.

15

It should be noted that the display may be of LCD type, LED type or another type. The display may moreover be adapted to show various forms of text messages. Icons may also be text.

20

Fig. 3a shows a first diagram of a state machine for visual programming of a toy element. The state machine is implemented as a program which can be executed by the microprocessor 102. When the state machine does not execute a user-specified program, and when the toy element has been turned on, activation of the key "select" will direct focus from one group of icons to another group of icons. That a group of icons is in focus may be shown by flashing an icon in a group or all the icons in a group. The state machine shown comprises three states 301, 302

30

PCT/DK00/00051

and 303 corresponding to switching focus between three different groups of icons.

5 The state machine changes states when the keys "select" or "shift" are activated. When the key "select" is activated, switching takes place between the states 301, 302 and 303. When the key "shift" is activated, the state machine continues in another set of states shown in fig. 3b.

10

It should be noted that just three states are indicated in this program, corresponding to three groups of icons on the display 201. This has been chosen in order to make the diagram readily understandable. In practice, there must be a number of states corresponding to the number of groups of icons on the display.

15

Fig. 3b shows a second diagram of a state machine for visual programming of a toy element. The state machine is caused to assume these states when the key "shift" is activated. It is assumed that a group of icons has been focused. When "shift" is activated, the state machine assumes the state 304 in which the first icon in the group which has been focused is activated - the other icons in the same group are not shown.

20

25

If the key "select" is activated, the state machine assumes the state 305 where "rule #1" is selected. "Rule #1" corresponds to a set of instructions for the micro-processor 102 which can perform a pattern of movement as shown on the icon "icon #1". Then the state machine assumes the state 306 where focus is moved from the current group of icons to another group of icons for the selection of an icon in this group.

30

Alternatively, if the key "shift" is selected in the state 304, the state machine assumes the state 307, where the "icon #2" is shown on the display - the other icons in the same group are not shown. Like in the state 304, it is possible in the state 307 to select a rule corresponding to the icon. This is done by activating the key "select", and then the state machine assumes the state 308 for the selection of the rule "rule #2". Subsequently, in state 309 focus is moved to the next group of icons.

Correspondingly, "icon #3" may be displayed in state 310 by activation of "shift". "Rule #3" may be selected by activation of "select", following which focus is moved to another group.

A further activation of "shift" in the state 310 causes all the icons in the group to be shown, and then the icons in the group are shown individually as described above.

In the states 306, 309 and 312, activation of the key "shift" will cause the state machine to assume one of the respective states 302 or 303 or 301.

It should be noted that it is also possible not to select a rule in one or more groups. In alternative embodiments, it can moreover be made possible to select several rules in the same group.

Additionally, it should be noted that this diagram corresponds to a display with just three icons in each group. This has been chosen to make the diagram readily under-

standable. In practice, there must be a number of states corresponding to the number of icons in a given group.

Generally, activation of the key "run" 114 will cause the state machine to assume a state in which a program is executed - irrespective of the number of selected rules. Thus, it is not necessary to ask the user whether the program is ready or not.

10 It is possible to jump to a desired group of icons in order just to change a rule in a user-specified program consisting of several rules.

Fig. 3c shows a third diagram for the interruption of a state machine. This diagram shows how the state machine in state 314, upon activation of "interrupt", stores a representation of the state T in which the microprocessor/state machine is present. It is hereby possible to resume a suddenly interrupted programming course without having to start from scratch. The toy element is turned off in state 315.

Fig. 3d shows a fourth diagram for starting a state machine. This diagram shows how the state machine, upon activation of "start", turns on the toy element in state 316. Then, a previously stored state representation T is retrieved in state 317. In state 318, the icons representing the state T are shown. In state 319, the icons in group 1 are focused, and then the state machine is ready for operation as described in connection with figs. 3a, 3b and 3c.

As will appear from the above description of figs. 3a, 3b, 3c and 3d, the user can program the toy element in a

simple manner to execute programs which comprise complicated functions. The programs are generated by combining a number of specific rules.

- 5 The state machine described above may be implemented in a very compact manner. It is ensured hereby that sophisticated and user-specified functions can be performed in response to a simple dialogue with the user.
- 10 In the states where a rule is selected, that is the states 305, 308 and 311, the program system 119 executes a number of operations, thereby generating a user-specified program which can be executed by the microprocessor 102.
- 15 The user-specified program can be generated by storing a reference (that is a pointer) in the memory 121 which refers to a rule stored in the memory 120. When several rules are selected to be included in the same user-specified program, a list of references to rules in the memory 120 is stored in the memory 121. A user-specified program may thus comprise one or more rules.
- 20
- Alternatively, the user-specified program may be generated by making a copy of each of the selected rules in the memory 120 and inserting the copies into the memory 121; the memory 121 will hereby contain a complete program. Furthermore, the user-specified program may be generated as a combination of references to rules and instructions to the microprocessor 102.
- 25
- 30

It should be noted that each rule typically comprises a set of instructions which may be considered a subprogram, a function or a procedure. But a rule may also just com-

prise modification of a parameter e.g. a parameter which indicates the speed of a connected motor or a time constant.

- 5 In an expedient embodiment of the invention, a given action may be performed when the state machine changes from a first state to a second state. An action may e.g. comprise signalling with sound and/or light to the user to indicate the state or type of state which the toy element  
10 has assumed.

Fig. 4 shows parallel and sequential execution of programs. When a user-specified program is generated, the rules may be executed as a sequence of rules, in parallel  
15 or in a combination of sequential and parallel program execution.

An example of two rules to be executed in parallel in time may be a first rule that a vehicle is to search for  
20 light, and a second rule that the vehicle is to change its direction when it detects obstacles.

An example of two rules to be performed sequentially in time may be a first rule that a vehicle is to drive  
25 straight ahead, and a second rule that the vehicle is to drive in a circular movement.

Rules R1 401, R2 402, R3 406, R4 405, R5 403 and R6 404 provide an example of a combination of sequential and  
30 parallel program execution.

When rules are executed as subprograms run in parallel in time, or in some form of time division between the subprograms, it must be possible to handle situations in

which several rules want access to a resource e.g. in the form of a motor. In a preferred embodiment, such a situation is handled by allocating a priority number to each of the rules which may be selected. For example, rules within the same group of icons on the display may be given the same priority number. When the operating system 118 detects that two rules or subprograms both want access to a resource within a period of time, the rule having the lowest priority number is interrupted or stopped. The rule with the highest priority number is then allowed to use the resource. If only one rule can be selected from the same group of icons, a unique and predictable program execution of user-specified programs is thus achieved.

Fig. 5 shows first and second toy elements, where the first toy element can transfer programs to the second toy element. The first toy element 501 comprises a microprocessor 507, a I/O module 510, a memory 509 and a user interface 508. The toy element 501 moreover comprises a two-way communications unit 506 for communication via an infrared transmitter/receiver 505 or for communication by means of a light source/light detector 504 which can emit and detect visible light.

Correspondingly, the second toy element 502 comprises a microprocessor 514, a I/O module 515 and a memory 516. The toy element 502 moreover comprises a communications unit 513 for communication via an infrared transmitter/receiver 512 or for communication by means of a light source/light detector 511 which can emit and detect visible light.

In a preferred embodiment of the invention, the first toy element can both transmit and receive data, while the second toy element can only receive data.

5 Data can be transferred as visible light via a light guide 503. Alternatively, data may be transferred as infrared light 517 and 518. Data may be in the form of codes that indicate a specific instruction and associated parameters which can be interpreted by the microproces-  
10 sors 507 and/or 514. Alternatively, data may be in the form of codes which refer to a subprogram or rule stored in the memory 516.

The I/O modules 510 and 515 may be connected to elec-  
15 tronic units (e.g. motors) for control of these. The I/O modules 510 and 515 may also be connected to electronic sensors so that the units may be controlled in response to detected signals.

20 In a preferred embodiment, the fibre 503 is adapted such that part of the visible light transmitted by it escapes from the fibre. It is hereby possible for a user - directly - to watch the transmission. The user can e.g. see when the communication begins and stops.

25 The light through the fibre can transfer data with a given data transmission frequency as changes in the light level in the fibre. Data may be transmitted such that it is possible for the user to observe individual light  
30 level changes during a transmission (that is at a suitably low data transmission frequency), or merely by seeing whether the transmission is going on (that is at a suitably high data transmission frequency).



Generally, it is undesirable that part of the light to be transmitted through the fibre escapes from the fibre. But in connection with communication between two toy elements, it is a desired effect, since it is then possible to watch the communication in a very intuitive manner.

It is known to a skilled person how to ensure that part of the light escapes from the fibre. It can e.g. be done by imparting impurities to the sheath of the fibre, or by making mechanical notches or patterns in the fibre. The part of the light which is to escape from the fibre may also be controlled by controlling the ratio of the refractive index of a core to that of a sheath of a light guide.

Fig. 6 shows a toy structure comprising a microprocessor controlled toy building element according to the invention coupled together with generally known toy building elements. The microprocessor controlled toy building element 601 is coupled on top of a structure 605 of building elements and two motors (not shown). The motors drive a wheel at each side of the vehicle, of which only the wheel 604 on one side of the toy structure is visible. The wheels are driven by a shaft 604 which is connected with the motor via gear wheels 603. The motors are electrically connected to the toy building element 601 by means of wires 615.

The toy structure moreover comprises two movable arms 606 which are pivotable about a bearing 607, so that the arms, when being pivoted, can be caused to affect a set of switches 608. The switches 608 are electrically connected to the toy element 601 via wires 609.

5

10

3134022  
 3134023  
 3134024  
 3134025  
 3134026  
 3134027  
 3134028  
 3134029  
 3134030  
 3134031  
 3134032  
 3134033  
 3134034  
 3134035  
 3134036  
 3134037  
 3134038  
 3134039  
 3134040  
 3134041  
 3134042  
 3134043  
 3134044  
 3134045  
 3134046  
 3134047  
 3134048  
 3134049  
 3134050  
 3134051  
 3134052  
 3134053  
 3134054  
 3134055  
 3134056  
 3134057  
 3134058  
 3134059  
 3134060  
 3134061  
 3134062  
 3134063  
 3134064  
 3134065  
 3134066  
 3134067  
 3134068  
 3134069  
 3134070  
 3134071  
 3134072  
 3134073  
 3134074  
 3134075  
 3134076  
 3134077  
 3134078  
 3134079  
 3134080  
 3134081  
 3134082  
 3134083  
 3134084  
 3134085  
 3134086  
 3134087  
 3134088  
 3134089  
 3134090  
 3134091  
 3134092  
 3134093  
 3134094  
 3134095  
 3134096  
 3134097  
 3134098  
 3134099  
 3134100  
 3134101  
 3134102  
 3134103  
 3134104  
 3134105  
 3134106  
 3134107  
 3134108  
 3134109  
 3134110  
 3134111  
 3134112  
 3134113  
 3134114  
 3134115  
 3134116  
 3134117  
 3134118  
 3134119  
 3134120  
 3134121  
 3134122  
 3134123  
 3134124  
 3134125  
 3134126  
 3134127  
 3134128  
 3134129  
 3134130  
 3134131  
 3134132  
 3134133  
 3134134  
 3134135  
 3134136  
 3134137  
 3134138  
 3134139  
 3134140  
 3134141  
 3134142  
 3134143  
 3134144  
 3134145  
 3134146  
 3134147  
 3134148  
 3134149  
 3134150  
 3134151  
 3134152  
 3134153  
 3134154  
 3134155  
 3134156  
 3134157  
 3134158  
 3134159  
 3134160  
 3134161  
 3134162  
 3134163  
 3134164  
 3134165  
 3134166  
 3134167  
 3134168  
 3134169  
 3134170  
 3134171  
 3134172  
 3134173  
 3134174  
 3134175  
 3134176  
 3134177  
 3134178  
 3134179  
 3134180  
 3134181  
 3134182  
 3134183  
 3134184  
 3134185  
 3134186  
 3134187  
 3134188  
 3134189  
 3134190  
 3134191  
 3134192  
 3134193  
 3134194  
 3134195  
 3134196  
 3134197  
 3134198  
 3134199  
 3134200  
 3134201  
 3134202  
 3134203  
 3134204  
 3134205  
 3134206  
 3134207  
 3134208  
 3134209  
 3134210  
 3134211  
 3134212  
 3134213  
 3134214  
 3134215  
 3134216  
 3134217  
 3134218  
 3134219  
 3134220  
 3134221  
 3134222  
 3134223  
 3134224  
 3134225  
 3134226  
 3134227  
 3134228  
 3134229  
 3134230  
 3134231  
 3134232  
 3134233  
 3134234  
 3134235  
 3134236  
 3134237  
 3134238  
 3134239  
 3134240  
 3134241  
 3134242  
 3134243  
 3134244  
 3134245  
 3134246  
 3134247  
 3134248  
 3134249  
 3134250  
 3134251  
 3134252  
 3134253  
 3134254  
 3134255  
 3134256  
 3134257  
 3134258  
 3134259  
 3134260  
 3134261  
 3134262  
 3134263  
 3134264  
 3134265  
 3134266  
 3134267  
 3134268  
 3134269  
 3134270  
 3134271  
 3134272  
 3134273  
 3134274  
 3134275  
 3134276  
 3134277  
 3134278  
 3134279  
 3134280  
 3134281  
 3134282  
 3134283  
 3134284  
 3134285  
 3134286  
 3134287  
 3134288  
 3134289  
 3134290  
 3134291  
 3134292  
 3134293  
 3134294  
 3134295  
 3134296  
 3134297  
 3134298  
 3134299  
 3134300  
 3134301  
 3134302  
 3134303  
 3134304  
 3134305  
 3134306  
 3134307  
 3134308  
 3134309  
 3134310  
 3134311  
 3134312  
 3134313  
 3134314  
 3134315  
 3134316  
 3134317  
 3134318  
 3134319  
 3134320  
 3134321  
 3134322  
 3134323  
 3134324  
 3134325  
 3134326  
 3134327  
 3134328  
 3134329  
 3134330  
 3134331  
 3134332  
 3134333  
 3134334  
 3134335  
 3134336  
 3134337  
 3134338  
 3134339  
 3134340  
 3134341  
 3134342  
 3134343  
 3134344  
 3134345  
 3134346  
 3134347  
 3134348  
 3134349  
 3134350  
 3134351  
 3134352  
 3134353  
 3134354  
 3134355  
 3134356  
 3134357  
 3134358  
 3134359  
 3134360  
 3134361  
 3134362